

1-866-430-6202

T6000

HIGH-PERFORMANCE THERMAL PRINTER

SPEED

VERSATILITY

RELIABILITY







The Powerful T6000 represents the next generation industrial, high-performance thermal barcode printer.

Setting new benchmarks for speed, print quality, validation and reliability, the T6000 is engineered with the singular mission of increasing true productivity and lowering compliance fees. Loaded with advanced features, validation technology, RFID capabilities and the most comprehensive emulation package available, the T6000 delivers supercharged performance for a wide array of applications.



SPEED

- Stellar quality print at lighting fast speed, clocking in at 14 ips
- Increased productivity at every shift as a direct result of the ARM Cortex-A9 controller, processing barcode data faster than ever before
- Ease-of-Use and an interactive screen reduces training and down time, helping your business focus on operational productivity



VERSATILITY

- Plug-n-Play in any operational environment, with the ability to be networked via the most comprehensive printer emulations in the industry
- Rugged design allows the T6000 to perform in even the most challenging environmental conditions
- Wide-ranging RFID support for On-Pitch, Short-Pitch and Standard Pitch to handle a variety of applications



RELIABILITY

- Exclusive validation solutions eliminate expensive compliance fees by producing 100% quality barcodes, 100% of the time
- Comprehensive WiFi security suite featuring the very latest protocols to block unauthorized access and ensure peace of mind
- Intelligent heat management system increases printhead life and improves barcode print quality while reducing operating costs

REAL WORLD BUSINESS APPLICATIONS THAT GIVE YOU THE EDGE ON YOUR COMPETITORS

- With industry-leading validation technologies like ODV that support the latest compliance labeling requirements your supply chain is now fortified with cutting-edge traceability applications that also eliminate costly compliance fines
- Easy integration in any legacy environment with full provisions for any Warehouse Management System helping you increase uptime and prevent loss of productivity
- Powers through the most rigorous shifts while handling multiple label applications- from 'Pick and Pack' support and cross-docking applications to labels for cases, pallets, packages, shipment slips, invoices, etc.

POSTSCRIPT/PDF FOR YOUR MOST COMPLEX LABELING NEEDS

- The T6000 is engineered to support all major ERP systems
- Plug-n-Play with native SAP drivers to expand your operational abilities
- Full range of fonts and symbols gives you the tools required to customize your labels to suit your unique application and environment

PRINTNET ENTERPRISE AUTO ID:

- Printronix Auto ID provides a unique remote printer management tool to monitor, configure and support printers from anywhere in the world
- Instant email and mobile phone alerts allow you to mitigate issues or designate events in real-time, maintaining continuous network health and peak performance
- Fully compatible with any Printronix Auto ID product

GENUINE PRINTRONIX SUPPLIES:

Our commitment to your particular application does not end at your printer. Instead, our promise of reliability continues throughout the life of your application and with every single printout. Genuine Printronix Supplies meet the stringent performance standards required by our printers and ensure optimum performance at every shift, every single day. With extensive manufacturing capabilities and multiple distribution points, our product experts can deliver custom solutions for a wide variety of applications.

SAY GOODBYE TO BAD BARCODES. With compliance fines as high as \$10,000, it is more critical than ever to print clean, readable barcodes. Online Data Validator (ODV) reads every barcode as it's printed. And if there is an error, the printer strikes through the bad barcode and reprints a new one.



T6000 SPECIFICATIONS

PRODUCT BENEFITS

- * High performance ARM Cortex-A9
 * Dia cost of unions from a union from a union of the second s
- * Die-cast aluminum frame w/metal door
- * Transfer and direct printing* 4" and 6" model configurations
- * Premium Asian and Andale font support

PRINTER SPECIFICATIONS

Max Print Speed (4"/6") Print Method Resolution Max. Print Width Printer Memory

MEDIA SPECIFICATIONS

Media Type Min. Media Width (4"/6") Max. Media Width Min. Media Length Max. Media Length Media Thickness Media Roll Core Diameter Max. Media Roll Diameter Media Sensing

RIBBON SPECIFICATIONS

Ribbon Type Min. Ribbon Width (4"/6") Max. Ribbon Width (4"/6") Max. Ribbon Length

PHYSICAL CHARACTERISTICS

Width (4"/6") Height (4"/6") Depth (4"/6") Printer Weight (4"/6") Shipping Weight (4"/6")

nt (4"/6") ight (4"/6")

PRINTER LANGUAGE IGP Languages Job Control Languages Optional Languages

PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL PJL, XML, and PTX-SETUP IPDS TN5250 PDF Level 1.7, Postscript Level 3

* State-of-the-art WiFi connectivity

* Available in 203 DPI and 300 DPI

* 512MB RAM / 128MB Flash Memory

* 4-32 GB SD memory card capability
 * ENERGY STAR Certified

14/12 IPS @ 203 DPI; 12/10 IPS @ 300 DPI

Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets

0.25" / 1.0" (Continuous/Tear-Off) / 0.5" (Peel-Off)

Transfer and Direct

4.1" (104mm) / 6.6" (168mm) 512MB RAM / 128MB Flash

1" (25.4mm)/2" (50.8mm)

Up to 99"

8.0" (209mm)

Gap, Mark

450 Meters

4.5" (114.3mm) / 6.8" (172.7mm)

2.5 Mil (0.0025") to 10 Mil (0.010")

1.5" (37.5mm) to 3.0" (76mm)

Wax, Wax/Resin, Resin

1" (25.4mm)/2" (50.8mm

4.5" (114.3mm)/6.8" (172.7mm)

10.9" (276.9mm)/14.1" (358.1mm)

12.3" (312.4mm)/12.4" (314.9mm) 20.3" (515.6mm)/20.3" (515.6mm)

33.6 lbs. (14.5Kg)/39 lbs. (17.4Kg)

42.6 lbs. (18.6Kg)/48 lbs. (21.5Kg)

203 DPI / 300 DPI

COMMUNICATION AND CONNECTIVITY/INTERFACE

Standard Interface I/O Optional Interface I/O WiFi Security Protocol

CONNECTIVITI/INTERFACE		
	Serial RS232, USB, and Ethernet 10/100Base T	
	Parallel, WiFi (802.11a/b/g/n), GPIO	
	WEP 40/128bit, WPA Personal (PSK),	
	WPA2 Personal (PSK) and Enterprise (AES CCMP)	
	EAP-TLS, EAP-TTLs, PEAPv0/MS-CHAPv2, PEAPv1	
	EAP-MD5	
DES		
	Continuous, Tear-Off Strip, Tear-Off	

MEDIA HANDLING MODES

Standard Options Continuous, Tear-Off Strip, Tear-Peel-Off, Cut, and Rewind



Contact your local Printronix Auto ID authorized reseller.





BARCODE VALIDATION

Online Data Validator (ODV)	Validates, Grade, Report, and Overstrike bar codes Supports 1D Barcodes (Picket Fence) Compatible with RFID encoding		
RFID			
UHF EPC Gen2 / ISO18000-6C	Multi-position RF antenna, Advanced Printer Encoder Firmware encodes and validates Gen2 compliant tags On-Pitch label to 0.625 in (depending on inlay) PGL, ZPL, STGL, MGL language support Counters track good / bad label encoding		
OPERATING ENVIRONMENT			
Operating Temperature Operating Humidity Storage Temperature Storage Humidity POWER REQUIREMENT	40 to 104 °F (5 to 40 °C) 20 - 85% Non-Condensing 23 to 140 °F (-5 to 60 °C) 5 - 85% Non-Condensing		
Line Input	Auto Range 100 - 264 VAC (48 - 62 Hz)		
	······		
REGULATORY COMPLIANCES Emissions Safety Environmental Radios (WiFi/RFID)	FCC, CE, CCC cTUVus, CE, EAC, SABS, RCM, CCC, KCC, S-MARK, NOM RoHS, WEEE, Energy Star FCC, CE, IC, and others based on market need		
BAR CODE SYMBOLOGIES			
1D Barcodes 2D Barcodes	BC-412, Code 11, Code 39, Code 35, Code 93, Codabar, Code128 Subsets A/B/C, Industrial 2 of 5, Interleave 2 of 5, German I-2/5, EAN-8, EAN-13, UCC/EAN-128, UPC-A, UPC-E, UPCSHIP, UPS 11, MSI, Matrix 2 of 5, PLESSEY, POSTNET, 4-state PostBar, Australian 4-state, FIM, ITF14, TELEPEN, PLANET, USPS Intelligent Mail, LOGMARS PDF-417, MicroPDF-417, Maxicode, DataMatrix, QR Codes, Aztec, GS1 Databar (RSS-14)		
FONT, GRAPHIC SUPPORT			
Graphic Formats Font Technologies Standard Fonts Asian Fonts (Optional SD card) Andale Fonts (Optional SD card) PDF/ PostScript Level 3	PCX, TIFF, BMP, PNG Intellifont, TrueType, Unicode OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate/Bold/Condensed Simplified Chinese, Japanese, and Korean Simplified Chinese, Traditional Chinese, Korean, Japanese 35 Fonts		
REMOTE MANAGEMENT SOFTWARE			
PrintNet Enterprise Auto ID	Enterprise Grade Remote Management Solution		
OPTIONS AND ACCESSORIES			
 WiFi 802.11 a/b/g/n (US/EU/CAN) Parallel Port GPIO TN5250 PDF/PostScript IPDS Online Data Validator (ODV) 	 Rewind 4"/6" Heavy Duty Cutter 4"/6" Peel & Present 4"/6" Premium Asian Font Cards Andale Font Cards QCMC (SD Quick Change Memory Card) UHF RFID (US 902-928MHz, EU 866-868MHz) 		





© 2016 Printronix Auto ID, Inc. All rights reserved. Printronix Auto ID and all product names, numbers and logos are trademarks or registered trademarks of Printronix, Inc. Product appearance and/or specifications are subject to change without notice. Windows^{*} is a registered trademark of Microsoft Corporation[™] in the United States and other countries. All other trademarks, product names and company names and logos herein, are the property of their respective owners. (8/16)