



ZT510™  
Industrial Printer

## ZT510 vs. 105SL*Plus* Comparison Guide

Building on the legacy of its industry-leading 105SL*Plus* predecessor, the ZT510 strikes the ideal balance between exceptional performance and budget-friendly value. It provides the outstanding durability and reliability you expect from a Zebra printer, plus next-generation printing capabilities, advanced management and monitoring, and future-ready adaptability to power through every challenge in the years to come. Below is an overview of the ZT510's advantages.

### User-Friendly Design

- Customizable, backlit, multi-line display including an intuitive menu, easy-to-use keypad and password protection
- Fast processing for quick throughput of even complex formats and graphic-based labels
- Dynamic QR codes that link to error-specific help videos

### Future-Ready Adaptability

- Flexible design that allows hardware updates in the field, including cutter and peeler
- Two open communication slots to easily add connectivity options, including 802.11a/c, Parallel, IPv6\* and USB Host

### Printer Integration and Management

- Cloud-accessible Link-OS® Printer Profile Manager Enterprise to manage routing, firmware and more, on-site or remotely
- Mobile Device Management connectors to integrate networked printers into AirWatch or SOTI Device Management systems
- Operational Visibility Services (OVS) & Asset Visibility Services (AVS) for real-time insight into printer status, utilization and functionality
- Near Field Communication (NFC), used with the Link-OS Print Touch app, that allows users to pair Android devices

## SIDE-BY-SIDE COMPARISON

ZT510 VS. 105SLPLUS

# Printer Comparison\*\*



Features	ZT510™		105SLPlus™	
Maximum Print Speed (per second)	203 dpi	12"/305 mm	203 dpi	12"/305 mm
	300 dpi	10"/254 mm	300 dpi	10"/254 mm
Maximum Print Width	4.09"/104 mm		4.09"/104 mm	
Standard Connectivity	<ul style="list-style-type: none"> <li>• Serial</li> <li>• USB</li> <li>• Gigabit Ethernet</li> <li>• Bluetooth® LE</li> </ul>		<ul style="list-style-type: none"> <li>• Serial</li> <li>• USB</li> <li>• Ethernet</li> <li>• Parallel</li> </ul>	
Optional Connectivity	<ul style="list-style-type: none"> <li>• Parallel</li> <li>• 802.11a/c with Bluetooth® 4.0</li> <li>• IPv6</li> <li>• USB Host</li> </ul>		<ul style="list-style-type: none"> <li>• ZebraNet 802.11b/g Print Server</li> </ul>	
Standard RAM	512 MB		16 MB	
Standard Flash	2 GB		8 MB	
User Interface	<ul style="list-style-type: none"> <li>• Backlit, monochrome graphical LCD</li> </ul>		<ul style="list-style-type: none"> <li>• Backlit, monochrome graphical LCD</li> </ul>	
Link-OS™ Enabled	Yes		No	
User Setup and Maintenance	<ul style="list-style-type: none"> <li>• Print Touch</li> <li>• Dynamic QR Codes</li> </ul>		None	



**NA and Corporate Headquarters**  
+1 800 423 0442  
inquiry4@zebra.com

**Asia-Pacific Headquarters**  
+65 6858 0722  
contact.apac@zebra.com

**EMEA Headquarters**  
zebra.com/locations  
mseurope@zebra.com

**Latin America Headquarters**  
+1 847 955 2283  
la.contactme@zebra.com